


XP-D451B

Thermal Barcode Printer

Xprinter®
www.xprinter.vn

XP-D451B

Direct Thermal Printer



Printer Specifications

Resolution	203 DPI
Print Method	Direct Thermal
Memory	8 MB RAM / 8 MB Flash
Max. Print Width	4.25 in./108 mm
Max. Print Speed	Up to 6 ips (152 mm/s)
Media Sensors	Fixed Black Mark Sensor / Fixed Gap Sensor / Fixed Label Position Sensor
Emulation	TSPL, ZPL, EPL, DPL
Interface	USB, Optional Wireless Connectivity: Bluetooth
Other	Doesn't Support RTC, Doesn't Support MicroSD Card Slot

Media and Ribbon Characteristics

Media Length	0.39 in. - 30 in. (10 mm - 762 mm)
Media Width	1 in. - 4.56 in. (25.4 mm - 116 mm)
Thickness	0.0023 in. (0.06 mm) Min.; 0.01 in. (0.254 mm) Max.
Media Types	Continuous, Gap, Black mark, Fan-fold, Perforated Media

Environment Condition

Operating Temp.	5~40°C (41~104°F)
Storage Temp.	-40~60°C (-40~140°F)
Operating Humidity	25 ~ 85% Non-Condensing
Storage Humidity	10 ~ 90% Non-Condensing

Fonts/Graphics/Symbologies

1D Bar Codes	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
2D Bar Codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Fonts and Graphics	Font 0 ~ Font 8

Software

Driver	Windows / Linux / Mac / Android / Chrome OS
SDK	Windows / Linux / Android / iOS
Software	Bartender UltraLite / Mobile Label Design App

Accessories

Standard Accessories	Power Adapter × 1, Power Cord × 1, USB Cable × 1, User Manual × 1
User Options	8" External Paper Roll Holder

Product Warranty

Printhead life	The earlier of 30 km usage or 1 year
Platen roller life	The earlier of 30 km usage or 1 year
Printer Warranty	1 Year

Physical Characteristics

Dimension	189 mm × 80 mm × 85 mm (D × W × H)
Weight	0.7 Kg



Quét mã QR Zalo Xprinter Vietnam để được hỗ trợ thêm thông tin.
Điện thoại: +84-09.3883.1717
Website: www.xprinter.vn
Email: contact@xprinter.vn



Suitable for Different Labels(Suitable size 1"-4.6")



Compatible with All Major Shipping and Sales Platforms

