

XP-P328B
Mobile Receipt & Label Printer

Xprinter
www.xprinter.vn


XP-P328B
Mobile Receipt & Label Printer



Printing	
Resolution	203 DPI
Printing method	Direct Thermal
Max.print speed	Max. 70mm (2.7") / s
Max.print width	72 mm (2.8")
Max.print length	1016mm (40")
Media	
Media type	Continuous, gap, black mark
Media width	30 mm ~ 80 mm
Media thickness	0.06 mm ~0.16 mm
Label roll diameter	50mm
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	USB+Bluetooth (Optional:USB+WIFI)
Screen	OLED (0.9") Resolution:128*64 pix
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°、 90°、 180°、 270°
Emulaion	ESC/POS, TSPL, CPCL, ZPL(Optional)
Physical Features	
Dimensions	114×103×59mm (D×W×H)
Weight	360 g
Reliability	
Printer head life	30Km
Software	
Operation system	Windows / Android / iOS
SDK	Windows / Android / iOS
Power supply	
Power input	Input: AC 100-240V, 0.5A 50-60Hz; Output: DC 5V/2A
Battery	7.4V / 2000mAh(Optional:2550mAh)
Environmental Conditions	
Operation environment	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C(-40~140°F), Humidity: 10 ~ 90% no condensing



- Support both label printing and receipt printing



- 50mm diameter paper roll




- Support direct USB charging



- Built-in paper bin, adjustable paper width



- 2000mAh battery life longer than other products



Quét mã QR Zalo Xprinter Vietnam để được hỗ trợ thêm thông tin.
Điện thoại: +84-09.3883.1717
Website: www.xprinter.vn
Email: contact@xprinter.vn

